

INVENTORY CONTROL FORM

Tibial Nail Advanced System

Case Information (eg, Case ID):

DO NOT PUT ANY
PATIENT IDENTIFIABLE
INFORMATION IN THIS FIELD

To order (USA): 800-523-0322

To order (Canada): 844-243-4321

Date: _____

Hospital: _____

Surgeon: _____

Procedure: _____

Implants

Tibial Nail Advanced System Ø 8 mm, Sterile

Length (mm)

	04.043.005S	255 mm
	04.043.010S	270 mm
	04.043.015S	285 mm
	04.043.020S	300 mm
	04.043.025S	315 mm
	04.043.030S	330 mm
	04.043.035S	345 mm
	04.043.040S	360 mm
	04.043.045S	375 mm
	04.043.050S	390 mm
	04.043.055S	405 mm
	04.043.060S	420 mm
	04.043.065S	435 mm
	04.043.070S	450 mm
	04.043.075S	465 mm



Tibial Nail Advanced System Ø 9 mm, Sterile

Length (mm)


	04.043.105S	255 mm
	04.043.110S	270 mm
	04.043.115S	285 mm
	04.043.120S	300 mm
	04.043.125S	315 mm
	04.043.130S	330 mm
	04.043.135S	345 mm
	04.043.140S	360 mm
	04.043.145S	375 mm
	04.043.150S	390 mm
	04.043.155S	405 mm
	04.043.160S	420 mm
	04.043.165S	435 mm
	04.043.170S	450 mm
	04.043.175S	465 mm



Tibial Nail Advanced System Ø 10 mm, Sterile

Length (mm)

	04.043.205S	255 mm
	04.043.210S	270 mm
	04.043.215S	285 mm
	04.043.220S	300 mm
	04.043.225S	315 mm
	04.043.230S	330 mm
	04.043.235S	345 mm
	04.043.240S	360 mm
	04.043.245S	375 mm
	04.043.250S	390 mm
	04.043.255S	405 mm
	04.043.260S	420 mm
	04.043.265S	435 mm
	04.043.270S	450 mm
	04.043.275S	465 mm



Tibial Nail Advanced System Ø 11 mm, Sterile

Length (mm)

	04.043.305S	255 mm
	04.043.310S	270 mm
	04.043.315S	285 mm
	04.043.320S	300 mm
	04.043.325S	315 mm
	04.043.330S	330 mm
	04.043.335S	345 mm
	04.043.340S	360 mm
	04.043.345S	375 mm
	04.043.350S	390 mm
	04.043.355S	405 mm
	04.043.360S	420 mm
	04.043.365S	435 mm
	04.043.370S	450 mm
	04.043.375S	465 mm



Tibial Nail Advanced System Ø 12 mm, Sterile

Length (mm)

	04.043.405S	255 mm
	04.043.410S	270 mm
	04.043.415S	285 mm
	04.043.420S	300 mm
	04.043.425S	315 mm
	04.043.430S	330 mm
	04.043.435S	345 mm
	04.043.440S	360 mm
	04.043.445S	375 mm
	04.043.450S	390 mm
	04.043.455S	405 mm
	04.043.460S	420 mm
	04.043.465S	435 mm
	04.043.470S	450 mm
	04.043.475S	465 mm



Tibial Nail Advanced System Ø 13 mm, Sterile

Length (mm)

	04.043.505S	255 mm
	04.043.510S	270 mm
	04.043.515S	285 mm
	04.043.520S	300 mm
	04.043.525S	315 mm
	04.043.530S	330 mm
	04.043.535S	345 mm
	04.043.540S	360 mm
	04.043.545S	375 mm
	04.043.550S	390 mm
	04.043.555S	405 mm
	04.043.560S	420 mm
	04.043.565S	435 mm
	04.043.570S	450 mm
	04.043.575S	465 mm



INVENTORY CONTROL FORM

Tibial Nail Advanced System

Implants (Continued)

*Available non sterile and sterile packed. Add "TS" to catalog number to order sterile product.

4.0mm Locking Screws for IM Nails

Locking Screws	Low Profile Locking Screw	Length (mm)
<input type="checkbox"/> 04.045.226*	<input type="checkbox"/> 04.045.526*	26 mm
<input type="checkbox"/> 04.045.228*	<input type="checkbox"/> 04.045.528*	28 mm
<input type="checkbox"/> 04.045.230*	<input type="checkbox"/> 04.045.530*	30 mm
<input type="checkbox"/> 04.045.232*	<input type="checkbox"/> 04.045.532*	32 mm
<input type="checkbox"/> 04.045.234*	<input type="checkbox"/> 04.045.534*	34 mm
<input type="checkbox"/> 04.045.236*	<input type="checkbox"/> 04.045.536*	36 mm
<input type="checkbox"/> 04.045.238*	<input type="checkbox"/> 04.045.538*	38 mm
<input type="checkbox"/> 04.045.240*	<input type="checkbox"/> 04.045.540*	40 mm
<input type="checkbox"/> 04.045.242*	<input type="checkbox"/> 04.045.542*	42 mm
<input type="checkbox"/> 04.045.244*	<input type="checkbox"/> 04.045.544*	44 mm
<input type="checkbox"/> 04.045.246*	<input type="checkbox"/> 04.045.546*	46 mm
<input type="checkbox"/> 04.045.248*	<input type="checkbox"/> 04.045.548*	48 mm
<input type="checkbox"/> 04.045.250*	<input type="checkbox"/> 04.045.550*	50 mm

5.0mm Locking Screws for IM Nails

Locking Screws	Low Profile Locking Screw	Length (mm)
<input type="checkbox"/> 04.045.026*	<input type="checkbox"/> 04.045.326*	26 mm
<input type="checkbox"/> 04.045.028*	<input type="checkbox"/> 04.045.328*	28 mm
<input type="checkbox"/> 04.045.030*	<input type="checkbox"/> 04.045.330*	30 mm
<input type="checkbox"/> 04.045.032*	<input type="checkbox"/> 04.045.332*	32 mm
<input type="checkbox"/> 04.045.034*	<input type="checkbox"/> 04.045.334*	34 mm
<input type="checkbox"/> 04.045.036*	<input type="checkbox"/> 04.045.336*	36 mm
<input type="checkbox"/> 04.045.038*	<input type="checkbox"/> 04.045.338*	38 mm
<input type="checkbox"/> 04.045.040*	<input type="checkbox"/> 04.045.340*	40 mm
<input type="checkbox"/> 04.045.042*	<input type="checkbox"/> 04.045.342*	42 mm
<input type="checkbox"/> 04.045.044*	<input type="checkbox"/> 04.045.344*	44 mm
<input type="checkbox"/> 04.045.046*	<input type="checkbox"/> 04.045.346*	46 mm
<input type="checkbox"/> 04.045.048*	<input type="checkbox"/> 04.045.348*	48 mm
<input type="checkbox"/> 04.045.050*	<input type="checkbox"/> 04.045.350*	50 mm
<input type="checkbox"/> 04.045.052*	<input type="checkbox"/> 04.045.352*	52 mm
<input type="checkbox"/> 04.045.054*	<input type="checkbox"/> 04.045.354*	54 mm
<input type="checkbox"/> 04.045.056*	<input type="checkbox"/> 04.045.356*	56 mm
<input type="checkbox"/> 04.045.058*	<input type="checkbox"/> 04.045.358*	58 mm
<input type="checkbox"/> 04.045.060*	<input type="checkbox"/> 04.045.360*	60 mm
<input type="checkbox"/> 04.045.062*	<input type="checkbox"/> 04.045.362*	62 mm
<input type="checkbox"/> 04.045.064*	<input type="checkbox"/> 04.045.364*	64 mm
<input type="checkbox"/> 04.045.066*	<input type="checkbox"/> 04.045.366*	66 mm
<input type="checkbox"/> 04.045.068*	<input type="checkbox"/> 04.045.368*	68 mm
<input type="checkbox"/> 04.045.070*	<input type="checkbox"/> 04.045.370*	70 mm
<input type="checkbox"/> 04.045.072*	<input type="checkbox"/> 04.045.372*	72 mm
<input type="checkbox"/> 04.045.074*	<input type="checkbox"/> 04.045.374*	74 mm
<input type="checkbox"/> 04.045.076*	<input type="checkbox"/> 04.045.376*	76 mm
<input type="checkbox"/> 04.045.078*	<input type="checkbox"/> 04.045.378*	78 mm
<input type="checkbox"/> 04.045.080*	<input type="checkbox"/> 04.045.380*	80 mm
<input type="checkbox"/> 04.045.082*	<input type="checkbox"/> 04.045.382*	82 mm
<input type="checkbox"/> 04.045.084*	<input type="checkbox"/> 04.045.384*	84 mm
<input type="checkbox"/> 04.045.086*	<input type="checkbox"/> 04.045.386*	86 mm
<input type="checkbox"/> 04.045.088*	<input type="checkbox"/> 04.045.388*	88 mm
<input type="checkbox"/> 04.045.090*	<input type="checkbox"/> 04.045.390*	90 mm
<input type="checkbox"/> 04.045.095*	<input type="checkbox"/> 04.045.395*	95 mm
<input type="checkbox"/> 04.045.100*	<input type="checkbox"/> 04.045.400*	100 mm

Locking Screws



Low Profile Locking Screws



End Caps, for TNNA

	Extensions (mm)
<input type="checkbox"/> 	<input type="checkbox"/> 04.045.850S 0 mm
<input type="checkbox"/> 	<input type="checkbox"/> 04.045.855S 5 mm
<input type="checkbox"/> 	<input type="checkbox"/> 04.045.860S 10 mm
<input type="checkbox"/> 	<input type="checkbox"/> 04.045.865S 15 mm

INVENTORY CONTROL FORM

Tibial Nail Advanced System

Instruments

Protection Sleeve for Suprapatellar Approach

03.043.033S	Protection Sleeve, for Nails \varnothing 8–11 mm, flexible, long, sterile
03.043.034S	Protection Sleeve, for Nails \varnothing 8–13 mm, flexible, long, sterile



Protection Sleeve with Tibial Fixation for Suprapatellar Approach

03.043.007S	Protection Sleeve, for Nails \varnothing 8–11 mm, flexible, Tibial Fixation, long, sterile
03.043.011S	Protection Sleeve, for Nails \varnothing 8–13 mm, flexible, Tibial Fixation, long, sterile



Trocar for Protection Sleeve for Suprapatellar Approach

03.043.008S	Trocar, for Nails \varnothing 8–11 mm, long, sterile
03.043.012S	Trocar, for Nails \varnothing 8–13 mm, long, sterile



Guide Wire with Stop for Protection Sleeve with Tibial Fixation for Suprapatellar Approach

03.043.013	Guide Wire, with Stop, \varnothing 3.2 mm
------------	---



INVENTORY CONTROL FORM









Tibial Nail Advanced System



PART OF THE *Johnson & Johnson* FAMILY OF COMPANIES

Instruments (Continued)


*Available non sterile and sterile packed. Add "S" to catalog number to order sterile product.

03.043.014*	12 mm Cannulated Drill Bit, short	03.010.100*	Drill Bit Ø 3.2 mm, length 145 mm, with Coupling for RDL
			
03.043.015*	12 mm Cannulated Drill Bit, long	03.010.103*	Drill Bit Ø 3.2 mm, length 145 mm, for Quick Coupling
			
03.043.016*	12 mm Cannulated Flexible Drill Bit, long	03.010.101*	Drill Bit Ø 4.2 mm, length 145 mm, with Coupling for RDL
			
03.045.022*	4.2 mm, Extra Long, calibrated	03.010.104*	Drill Bit Ø 4.2 mm, length 145 mm, for Quick Coupling
			

Reaming and Guide Roads

Part #	Description
351.704S	2.5 mm Reaming Rod with ball tip and extension, 1150 mm, sterile
351.706S	2.5 mm Reaming Rod with ball tip, 950 mm, sterile
351.707S	2.5 mm Reaming Rod with ball tip and extension, 950 mm, sterile
351.708S	2.5 mm Reaming Rod with ball tip and extension, 1150 mm, sterile
03.233.010S	3.0 mm Reaming Rod with 3.8 mm ball tip, 950 mm
03.233.011S	3.0 mm Reaming Rod with 3.8 mm ball tip, 1150 mm

Guide Wires

Part #	Description
357.399*	3.2 mm Guide Wire 400 mm
	
03.045.018*	3.2 mm Guide Wire 400 mm
