

Inventory Control Form

TFN Advanced

PROXIMAL FEMORAL NAILING SYSTEM



PART OF THE **Johnson & Johnson** FAMILY OF COMPANIES

Case Information (eg, Case ID):

DO NOT PUT ANY
PATIENT IDENTIFIABLE
INFORMATION IN
THIS FIELD

To order (USA): 800-523-0322

To order (Canada): 855-946-8999

Date: _____

Hospital: _____

Surgeon: _____

Procedure: _____

Implants

TFN-ADVANCED® System, Long Nails, 9 mm distal diameter, sterile



	RIGHT	LEFT	LENGTH	FEMORAL NECK ANGLE	
<input type="checkbox"/>	04.037.916S	<input type="checkbox"/>	04.037.917S	260	125°
<input type="checkbox"/>	04.037.918S	<input type="checkbox"/>	04.037.919S	280	125°
<input type="checkbox"/>	04.037.920S	<input type="checkbox"/>	04.037.921S	300	125°
<input type="checkbox"/>	04.037.922S	<input type="checkbox"/>	04.037.923S	320	125°
<input type="checkbox"/>	04.037.924S	<input type="checkbox"/>	04.037.925S	340	125°
<input type="checkbox"/>	04.037.926S	<input type="checkbox"/>	04.037.927S	360	125°
<input type="checkbox"/>	04.037.928S	<input type="checkbox"/>	04.037.929S	380	125°
<input type="checkbox"/>	04.037.930S	<input type="checkbox"/>	04.037.931S	400	125°
<input type="checkbox"/>	04.037.932S	<input type="checkbox"/>	04.037.933S	420	125°
<input type="checkbox"/>	04.037.934S	<input type="checkbox"/>	04.037.935S	440	125°
<input type="checkbox"/>	04.037.936S	<input type="checkbox"/>	04.037.937S	460	125°
<input type="checkbox"/>	04.037.938S	<input type="checkbox"/>	04.037.939S	480	125°
<input type="checkbox"/>	04.037.946S	<input type="checkbox"/>	04.037.947S	260	130°
<input type="checkbox"/>	04.037.948S	<input type="checkbox"/>	04.037.949S	280	130°
<input type="checkbox"/>	04.037.950S	<input type="checkbox"/>	04.037.951S	300	130°
<input type="checkbox"/>	04.037.952S	<input type="checkbox"/>	04.037.953S	320	130°
<input type="checkbox"/>	04.037.954S	<input type="checkbox"/>	04.037.955S	340	130°
<input type="checkbox"/>	04.037.956S	<input type="checkbox"/>	04.037.957S	360	130°
<input type="checkbox"/>	04.037.958S	<input type="checkbox"/>	04.037.959S	380	130°
<input type="checkbox"/>	04.037.960S	<input type="checkbox"/>	04.037.961S	400	130°
<input type="checkbox"/>	04.037.962S	<input type="checkbox"/>	04.037.963S	420	130°
<input type="checkbox"/>	04.037.964S	<input type="checkbox"/>	04.037.965S	440	130°
<input type="checkbox"/>	04.037.966S	<input type="checkbox"/>	04.037.967S	460	130°
<input type="checkbox"/>	04.037.968S	<input type="checkbox"/>	04.037.969S	480	130°

TFN-ADVANCED System, Long Nails, 10 mm distal diameter, sterile



	RIGHT	LEFT	LENGTH	FEMORAL NECK ANGLE	
<input type="checkbox"/>	04.037.016S	<input type="checkbox"/>	04.037.017S	260	125°
<input type="checkbox"/>	04.037.018S	<input type="checkbox"/>	04.037.019S	280	125°
<input type="checkbox"/>	04.037.020S	<input type="checkbox"/>	04.037.021S	300	125°
<input type="checkbox"/>	04.037.022S	<input type="checkbox"/>	04.037.023S	320	125°
<input type="checkbox"/>	04.037.024S	<input type="checkbox"/>	04.037.025S	340	125°
<input type="checkbox"/>	04.037.026S	<input type="checkbox"/>	04.037.027S	360	125°
<input type="checkbox"/>	04.037.028S	<input type="checkbox"/>	04.037.029S	380	125°
<input type="checkbox"/>	04.037.030S	<input type="checkbox"/>	04.037.031S	400	125°
<input type="checkbox"/>	04.037.032S	<input type="checkbox"/>	04.037.033S	420	125°
<input type="checkbox"/>	04.037.034S	<input type="checkbox"/>	04.037.035S	440	125°
<input type="checkbox"/>	04.037.036S	<input type="checkbox"/>	04.037.037S	460	125°
<input type="checkbox"/>	04.037.038S	<input type="checkbox"/>	04.037.039S	480	125°
<input type="checkbox"/>	04.037.046S	<input type="checkbox"/>	04.037.047S	260	130°
<input type="checkbox"/>	04.037.048S	<input type="checkbox"/>	04.037.049S	280	130°
<input type="checkbox"/>	04.037.050S	<input type="checkbox"/>	04.037.051S	300	130°
<input type="checkbox"/>	04.037.052S	<input type="checkbox"/>	04.037.053S	320	130°
<input type="checkbox"/>	04.037.054S	<input type="checkbox"/>	04.037.055S	340	130°
<input type="checkbox"/>	04.037.056S	<input type="checkbox"/>	04.037.057S	360	130°
<input type="checkbox"/>	04.037.058S	<input type="checkbox"/>	04.037.059S	380	130°
<input type="checkbox"/>	04.037.060S	<input type="checkbox"/>	04.037.061S	400	130°
<input type="checkbox"/>	04.037.062S	<input type="checkbox"/>	04.037.063S	420	130°
<input type="checkbox"/>	04.037.064S	<input type="checkbox"/>	04.037.065S	440	130°
<input type="checkbox"/>	04.037.066S	<input type="checkbox"/>	04.037.067S	460	130°
<input type="checkbox"/>	04.037.068S	<input type="checkbox"/>	04.037.069S	480	130°

Inventory Control Form

TFN Advanced

PROXIMAL FEMORAL NAILING SYSTEM



PART OF THE **Johnson & Johnson** FAMILY OF COMPANIES

Implants (cont'd)

TFN-ADVANCED System, Long Nails, 11 mm distal diameter, sterile



	RIGHT		LEFT	LENGTH	FEMORAL NECK ANGLE
<input type="checkbox"/>	04.037.120S	<input type="checkbox"/>	04.037.121S	300	125°
<input type="checkbox"/>	04.037.122S	<input type="checkbox"/>	04.037.123S	320	125°
<input type="checkbox"/>	04.037.124S	<input type="checkbox"/>	04.037.125S	340	125°
<input type="checkbox"/>	04.037.126S	<input type="checkbox"/>	04.037.127S	360	125°
<input type="checkbox"/>	04.037.128S	<input type="checkbox"/>	04.037.129S	380	125°
<input type="checkbox"/>	04.037.130S	<input type="checkbox"/>	04.037.131S	400	125°
<input type="checkbox"/>	04.037.132S	<input type="checkbox"/>	04.037.133S	420	125°
<input type="checkbox"/>	04.037.134S	<input type="checkbox"/>	04.037.135S	440	125°
<input type="checkbox"/>	04.037.136S	<input type="checkbox"/>	04.037.137S	460	125°
<input type="checkbox"/>	04.037.138S	<input type="checkbox"/>	04.037.139S	480	125°
<input type="checkbox"/>	04.037.150S	<input type="checkbox"/>	04.037.151S	300	130°
<input type="checkbox"/>	04.037.152S	<input type="checkbox"/>	04.037.153S	320	130°
<input type="checkbox"/>	04.037.154S	<input type="checkbox"/>	04.037.155S	340	130°
<input type="checkbox"/>	04.037.156S	<input type="checkbox"/>	04.037.157S	360	130°
<input type="checkbox"/>	04.037.158S	<input type="checkbox"/>	04.037.159S	380	130°
<input type="checkbox"/>	04.037.160S	<input type="checkbox"/>	04.037.161S	400	130°
<input type="checkbox"/>	04.037.162S	<input type="checkbox"/>	04.037.163S	420	130°
<input type="checkbox"/>	04.037.164S	<input type="checkbox"/>	04.037.165S	440	130°
<input type="checkbox"/>	04.037.166S	<input type="checkbox"/>	04.037.167S	460	130°
<input type="checkbox"/>	04.037.168S	<input type="checkbox"/>	04.037.169S	480	130°
<input type="checkbox"/>	04.037.180S	<input type="checkbox"/>	04.037.181S	300	135°
<input type="checkbox"/>	04.037.182S	<input type="checkbox"/>	04.037.183S	320	135°
<input type="checkbox"/>	04.037.184S	<input type="checkbox"/>	04.037.185S	340	135°
<input type="checkbox"/>	04.037.186S	<input type="checkbox"/>	04.037.187S	360	135°
<input type="checkbox"/>	04.037.188S	<input type="checkbox"/>	04.037.189S	380	135°
<input type="checkbox"/>	04.037.190S	<input type="checkbox"/>	04.037.191S	400	135°
<input type="checkbox"/>	04.037.192S	<input type="checkbox"/>	04.037.193S	420	135°
<input type="checkbox"/>	04.037.194S	<input type="checkbox"/>	04.037.195S	440	135°
<input type="checkbox"/>	04.037.196S	<input type="checkbox"/>	04.037.197S	460	135°
<input type="checkbox"/>	04.037.198S	<input type="checkbox"/>	04.037.199S	480	135°

Titanium End Caps for TFN-ADVANCED System Nail, sterile

<input type="checkbox"/>	04.038.000S	0 mm Extension
<input type="checkbox"/>	04.038.005S	5 mm Extension
<input type="checkbox"/>	04.038.010S	10 mm Extension
<input type="checkbox"/>	04.038.015S	15 mm Extension



TFN-ADVANCED System, Long Nails, 12 mm distal diameter, sterile



	RIGHT		LEFT	LENGTH	FEMORAL NECK ANGLE
<input type="checkbox"/>	04.037.220S	<input type="checkbox"/>	04.037.221S	300	125°
<input type="checkbox"/>	04.037.222S	<input type="checkbox"/>	04.037.223S	320	125°
<input type="checkbox"/>	04.037.224S	<input type="checkbox"/>	04.037.225S	340	125°
<input type="checkbox"/>	04.037.226S	<input type="checkbox"/>	04.037.227S	360	125°
<input type="checkbox"/>	04.037.228S	<input type="checkbox"/>	04.037.229S	380	125°
<input type="checkbox"/>	04.037.230S	<input type="checkbox"/>	04.037.231S	400	125°
<input type="checkbox"/>	04.037.232S	<input type="checkbox"/>	04.037.233S	420	125°
<input type="checkbox"/>	04.037.234S	<input type="checkbox"/>	04.037.235S	440	125°
<input type="checkbox"/>	04.037.236S	<input type="checkbox"/>	04.037.237S	460	125°
<input type="checkbox"/>	04.037.238S	<input type="checkbox"/>	04.037.239S	480	125°
<input type="checkbox"/>	04.037.250S	<input type="checkbox"/>	04.037.251S	300	130°
<input type="checkbox"/>	04.037.252S	<input type="checkbox"/>	04.037.253S	320	130°
<input type="checkbox"/>	04.037.254S	<input type="checkbox"/>	04.037.255S	340	130°
<input type="checkbox"/>	04.037.256S	<input type="checkbox"/>	04.037.257S	360	130°
<input type="checkbox"/>	04.037.258S	<input type="checkbox"/>	04.037.259S	380	130°
<input type="checkbox"/>	04.037.260S	<input type="checkbox"/>	04.037.261S	400	130°
<input type="checkbox"/>	04.037.262S	<input type="checkbox"/>	04.037.263S	420	130°
<input type="checkbox"/>	04.037.264S	<input type="checkbox"/>	04.037.265S	440	130°
<input type="checkbox"/>	04.037.266S	<input type="checkbox"/>	04.037.267S	460	130°
<input type="checkbox"/>	04.037.268S	<input type="checkbox"/>	04.037.269S	480	130°

TFN-ADVANCED System, Long Nails, 14 mm distal diameter, sterile



	RIGHT		LEFT	LENGTH	FEMORAL NECK ANGLE
<input type="checkbox"/>	04.037.450S	<input type="checkbox"/>	04.037.451S	300	130°
<input type="checkbox"/>	04.037.452S	<input type="checkbox"/>	04.037.453S	320	130°
<input type="checkbox"/>	04.037.454S	<input type="checkbox"/>	04.037.455S	340	130°
<input type="checkbox"/>	04.037.456S	<input type="checkbox"/>	04.037.457S	360	130°
<input type="checkbox"/>	04.037.458S	<input type="checkbox"/>	04.037.459S	380	130°
<input type="checkbox"/>	04.037.460S	<input type="checkbox"/>	04.037.461S	400	130°
<input type="checkbox"/>	04.037.462S	<input type="checkbox"/>	04.037.463S	420	130°
<input type="checkbox"/>	04.037.464S	<input type="checkbox"/>	04.037.465S	440	130°
<input type="checkbox"/>	04.037.466S	<input type="checkbox"/>	04.037.467S	460	130°
<input type="checkbox"/>	04.037.468S	<input type="checkbox"/>	04.037.469S	480	130°

Inventory Control Form

TFN Advanced

PROXIMAL FEMORAL NAILING SYSTEM



PART OF THE **Johnson & Johnson** FAMILY OF COMPANIES

Implants (cont'd)

TFN-ADVANCED System, Short Nails, 170 mm length, sterile



		DIAMETER	FEMORAL NECK ANGLE
<input type="checkbox"/>	04.037.912S	9	125°
<input type="checkbox"/>	04.037.942S	9	130°
<input type="checkbox"/>	04.037.972S	9	135°
<input type="checkbox"/>	04.037.012S	10	125°
<input type="checkbox"/>	04.037.042S	10	130°
<input type="checkbox"/>	04.037.072S	10	135°
<input type="checkbox"/>	04.037.112S	11	125°
<input type="checkbox"/>	04.037.142S	11	130°
<input type="checkbox"/>	04.037.172S	11	135°
<input type="checkbox"/>	04.037.212S	12	125°
<input type="checkbox"/>	04.037.242S	12	130°
<input type="checkbox"/>	04.037.272S	12	135°

TFN-ADVANCED System, Short Nails, 200 mm length, sterile



		DIAMETER	FEMORAL NECK ANGLE
<input type="checkbox"/>	04.037.913S	9	125°
<input type="checkbox"/>	04.037.943S	9	130°
<input type="checkbox"/>	04.037.973S	9	135°
<input type="checkbox"/>	04.037.013S	10	125°
<input type="checkbox"/>	04.037.043S	10	130°
<input type="checkbox"/>	04.037.073S	10	135°
<input type="checkbox"/>	04.037.113S	11	125°
<input type="checkbox"/>	04.037.143S	11	130°
<input type="checkbox"/>	04.037.173S	11	135°
<input type="checkbox"/>	04.037.213S	12	125°
<input type="checkbox"/>	04.037.243S	12	130°
<input type="checkbox"/>	04.037.273S	12	135°

TFN-ADVANCED System, Short Nails, 235 mm length, sterile



	RIGHT	LEFT	DIAMETER	FEMORAL NECK ANGLE	
<input type="checkbox"/>	04.037.914S	<input type="checkbox"/>	04.037.915S	9	125°
<input type="checkbox"/>	04.037.944S	<input type="checkbox"/>	04.037.945S	9	130°
<input type="checkbox"/>	04.037.974S	<input type="checkbox"/>	04.037.975S	9	135°
<input type="checkbox"/>	04.037.014S	<input type="checkbox"/>	04.037.015S	10	125°
<input type="checkbox"/>	04.037.044S	<input type="checkbox"/>	04.037.045S	10	130°
<input type="checkbox"/>	04.037.074S	<input type="checkbox"/>	04.037.075S	10	135°
<input type="checkbox"/>	04.037.114S	<input type="checkbox"/>	04.037.115S	11	125°
<input type="checkbox"/>	04.037.144S	<input type="checkbox"/>	04.037.145S	11	130°
<input type="checkbox"/>	04.037.174S	<input type="checkbox"/>	04.037.175S	11	135°
<input type="checkbox"/>	04.037.214S	<input type="checkbox"/>	04.037.215S	12	125°
<input type="checkbox"/>	04.037.244S	<input type="checkbox"/>	04.037.245S	12	130°
<input type="checkbox"/>	04.037.274S	<input type="checkbox"/>	04.037.275S	12	135°

TFN-ADVANCED System Helical Blades^o



		LENGTH			LENGTH
<input type="checkbox"/>	04.038.370	70 mm	<input type="checkbox"/>	04.038.405	105 mm
<input type="checkbox"/>	04.038.375	75 mm	<input type="checkbox"/>	04.038.410	110 mm
<input type="checkbox"/>	04.038.380	80 mm	<input type="checkbox"/>	04.038.415	115 mm
<input type="checkbox"/>	04.038.385	85 mm	<input type="checkbox"/>	04.038.420	120 mm
<input type="checkbox"/>	04.038.390	90 mm	<input type="checkbox"/>	04.038.425	125 mm
<input type="checkbox"/>	04.038.395	95 mm	<input type="checkbox"/>	04.038.430	130 mm
<input type="checkbox"/>	04.038.400	100 mm			

TFN-ADVANCED System Screws^o



		LENGTH			LENGTH
<input type="checkbox"/>	04.038.170	70 mm	<input type="checkbox"/>	04.038.205	105 mm
<input type="checkbox"/>	04.038.175	75 mm	<input type="checkbox"/>	04.038.210	110 mm
<input type="checkbox"/>	04.038.180	80 mm	<input type="checkbox"/>	04.038.215	115 mm
<input type="checkbox"/>	04.038.185	85 mm	<input type="checkbox"/>	04.038.220	120 mm
<input type="checkbox"/>	04.038.190	90 mm	<input type="checkbox"/>	04.038.225	125 mm
<input type="checkbox"/>	04.038.195	95 mm	<input type="checkbox"/>	04.038.230	130 mm
<input type="checkbox"/>	04.038.200	100 mm			

5.0 mm Ti Locking Screws with T25 STARDRIVE™ Recess for IM Nails^o



		LENGTH			LENGTH
<input type="checkbox"/>	04.005.516	26 mm	<input type="checkbox"/>	04.005.542	52 mm
<input type="checkbox"/>	04.005.518	28 mm	<input type="checkbox"/>	04.005.544	54 mm
<input type="checkbox"/>	04.005.520	30 mm	<input type="checkbox"/>	04.005.546	56 mm
<input type="checkbox"/>	04.005.522	32 mm	<input type="checkbox"/>	04.005.548	58 mm
<input type="checkbox"/>	04.005.524	34 mm	<input type="checkbox"/>	04.005.550	60 mm
<input type="checkbox"/>	04.005.526	36 mm	<input type="checkbox"/>	04.005.554	64 mm
<input type="checkbox"/>	04.005.528	38 mm	<input type="checkbox"/>	04.005.558	68 mm
<input type="checkbox"/>	04.005.530	40 mm	<input type="checkbox"/>	04.005.562	72 mm
<input type="checkbox"/>	04.005.532	42 mm	<input type="checkbox"/>	04.005.566	76 mm
<input type="checkbox"/>	04.005.534	44 mm	<input type="checkbox"/>	04.005.570	80 mm
<input type="checkbox"/>	04.005.536	46 mm	<input type="checkbox"/>	04.005.575	85 mm
<input type="checkbox"/>	04.005.538	48 mm	<input type="checkbox"/>	04.005.580	90 mm
<input type="checkbox"/>	04.005.540	50 mm			

^oAvailable nonsterile or sterile-packed. Add "S" to catalog number to order sterile product.

Inventory Control Form

TFN Advanced

PROXIMAL FEMORAL NAILING SYSTEM

Implants (cont'd)

TRAUMACEM™ V+ Augmentation System Implants and Instruments

- 07.702.040S TRAUMACEM™ V+ Injectable Bone Cement, Sterile
- 03.702.150S TRAUMACEM™ V+ Syringe Kit, 4 x 1 mL, 2 x 2 mL, Sterile
- 03.702.121S TRAUMACEM™ V+ Injection Cannula, for TFNA System, Sterile

Instruments

Guide Wires

- 357.399 3.2 mm Guide Wire, 400 mm
- 09.037.010 3.2 mm Guide Wire, 475 mm

4.2 mm Three-Fluted Drill Bits, quick coupling

- 03.010.104 Quick Coupling/Needle Point/145 mm
- 03.010.104S Quick Coupling/Needle Point/145 mm, sterile
- 03.010.101 Radiolucent, Needle Point/145 mm
- 03.010.061 Quick Coupling/330 100 mm Calibration
- 03.010.061S Quick Coupling/330 100 mm Calibration, sterile

Instruments (cont'd)

Cannulated Drill Bits

- 03.037.002 16 mm Flexible Drill Bit
- 03.037.003 16 mm Drill Bit
- 03.037.004[◇] 16 mm Hollow Drill Bit
- 03.037.021 10 mm Tapered Drill Bit
- 03.037.022 6 mm/9 mm Cannulated Stepped Drill Bit
- 03.037.102 16 mm Percutaneous Flexible Drill Bit
- 03.037.103 16 mm Percutaneous Drill Bit
- 03.037.104[◇] 16 mm Percutaneous Hollow Drill Bit

Reaming and Guide Rods

- 351.71[◇] 3.0 mm Reaming Rod, 950 mm, with offset ball tip
- 351.76[◇] 3.0 mm Reaming Rod, 950 mm, with straight ball tip
- 351.704S 2.5 mm Reaming Rod with ball tip and extension, 1150 mm, sterile
- 351.706S 2.5 mm Reaming Rod with ball tip, 950 mm, sterile
- 351.707S 2.5 mm Reaming Rod with ball tip and extension, 950 mm, sterile
- 351.708S 2.5 mm Reaming Rod with ball tip, 1150 mm, sterile
- 355.041[◇] 3.0 mm Guide Rod, 950 mm, with smooth tip

[◇]Available nonsterile or sterile-packed. Add "S" to catalog number to order sterile product.

Some devices in this form may not have been licensed in accordance with Canadian law and may not be for sale in Canada. Please contact your sales consultant for items approved for sale in Canada.

 **DePuy Synthes**

PART OF THE  FAMILY OF COMPANIES

© DePuy Synthes 2017. All rights reserved.
DSUS/TRM/0617/1499 6/17 DV

Manufactured or distributed by:

Synthes USA Products, LLC
1302 Wrights Lane East
West Chester, PA 19380

Synthes USA, LLC
1101 Synthes Avenue
Monument, CO 80132

To order (USA): 800-523-0322
To order (Canada): 855-946-8999

Note: For recognized manufacturer, refer to the product label.

www.depuySynthes.com