

Inventory Control Form



2.4 mm/2.7 mm Titanium VA-LCP Forefoot/Midfoot Plating System

Patient Information:

Synthes (USA) To Order: (800) 523-0322	Synthes (Canada) Ltd. To Order: (800) 668-1119
---	---

Date: _____

Hospital: _____

Surgeon: _____

Procedure: _____

Implants

2.4 mm/2.7 mm Titanium VA-LCP First MTP Fusion Plates Small

<input type="checkbox"/>	04.211.230	0°	right
<input type="checkbox"/>	04.211.231	0°	left
<input type="checkbox"/>	04.211.232	5°	right
<input type="checkbox"/>	04.211.233	5°	left
<input type="checkbox"/>	04.211.234	10°	right
<input type="checkbox"/>	04.211.235	10°	left



Medium

<input type="checkbox"/>	04.211.236	0°	right
<input type="checkbox"/>	04.211.237	0°	left
<input type="checkbox"/>	04.211.238	5°	right
<input type="checkbox"/>	04.211.239	5°	left
<input type="checkbox"/>	04.211.240	10°	right
<input type="checkbox"/>	04.211.241	10°	left



Large

<input type="checkbox"/>	04.211.242	5°	right
<input type="checkbox"/>	04.211.243	5°	left



Revision

<input type="checkbox"/>	04.211.244	0°	right
<input type="checkbox"/>	04.211.245	0°	left



2.4 mm/2.7 mm Titanium VA-LCP TMT Fusion Plates

<input type="checkbox"/>	04.211.246	First TMT Fusion Plate, standard
<input type="checkbox"/>	04.211.247	First TMT Fusion Plate, large
<input type="checkbox"/>	04.211.266	TMT Fusion Plate



Titanium General Fusion Plates 2.4 mm/2.7 mm VA-LCP Cloverleaf Fusion Plates

<input type="checkbox"/>	04.211.250	Short
<input type="checkbox"/>	04.211.251	Standard
<input type="checkbox"/>	04.211.252	Long



2.4 mm/2.7 mm VA-LCP T-Fusion Plates

	HEAD HOLES		
<input type="checkbox"/>	04.211.253	2	short
<input type="checkbox"/>	04.211.254	2	standard
<input type="checkbox"/>	04.211.255	2	long
<input type="checkbox"/>	04.211.265	3	long



2.4 mm/2.7 mm VA-LCP L-Fusion Plates

<input type="checkbox"/>	04.211.256	Short	right
<input type="checkbox"/>	04.211.257	Short	left
<input type="checkbox"/>	04.211.258	Standard	right
<input type="checkbox"/>	04.211.259	Standard	left
<input type="checkbox"/>	04.211.260	Long	right
<input type="checkbox"/>	04.211.261	Long	left



2.4 mm/2.7 mm VA-Locking X-plates

<input type="checkbox"/>	04.211.201	Extra Small
<input type="checkbox"/>	04.211.202	Small
<input type="checkbox"/>	04.211.203	Medium
<input type="checkbox"/>	04.211.204	Large



2.4 mm/2.7 mm Titanium VA-LCP Forefoot/Midfoot Plating System

Implants (cont'd)

2.4 mm/2.7 mm VA-Locking Straight Fusion Plates

		HOLES
<input type="checkbox"/>	04.211.262	2
<input type="checkbox"/>	04.211.263	4



2.4 mm/2.7 mm VA-Locking Opening Wedge Plates

		SPACER
<input type="checkbox"/>	04.211.210	No Spacer
<input type="checkbox"/>	04.211.211	3 mm
<input type="checkbox"/>	04.211.212	4 mm
<input type="checkbox"/>	04.211.213	5 mm
<input type="checkbox"/>	04.211.214	6 mm
<input type="checkbox"/>	04.211.215	7 mm



2.4 mm/2.7 mm Titanium VA-Locking Tarsal and Mesh Plates


<input type="checkbox"/>	04.211.220	2.4 mm/2.7 mm VA-Locking Navicular Plate
--------------------------	------------	--



<input type="checkbox"/>	04.211.221	2.4 mm/2.7 mm VA-Locking Cuboid Plate, left
<input type="checkbox"/>	04.211.222	2.4 mm/2.7 mm VA-Locking Cuboid Plate, right



<input type="checkbox"/>	04.211.224	2.4 mm/2.7 mm VA-Locking Mesh Plate, 5X12 holes
--------------------------	------------	---



1.6 mm Compression Wires



		THREAD LENGTH	TOTAL LENGTH
<input type="checkbox"/>	03.211.410	10 mm	150 mm
<input type="checkbox"/>	03.211.415	15 mm	150 mm
<input type="checkbox"/>	03.211.420	20 mm	150 mm
<input type="checkbox"/>	03.211.425	25 mm	150 mm
<input type="checkbox"/>	03.211.430	30 mm	150 mm
<input type="checkbox"/>	03.211.435	35 mm	150 mm
<input type="checkbox"/>	03.211.440	40 mm	150 mm

2.7 mm Titanium Variable Angle Locking Screws, self-tapping, with T8 StarDrive recess



		LENGTH			LENGTH
<input type="checkbox"/>	04.211.010	10 mm	<input type="checkbox"/>	04.211.036	36 mm
<input type="checkbox"/>	04.211.012	12 mm	<input type="checkbox"/>	04.211.038	38 mm
<input type="checkbox"/>	04.211.014	14 mm	<input type="checkbox"/>	04.211.040	40 mm
<input type="checkbox"/>	04.211.016	16 mm	<input type="checkbox"/>	04.211.042	42 mm
<input type="checkbox"/>	04.211.018	18 mm	<input type="checkbox"/>	04.211.044	44 mm
<input type="checkbox"/>	04.211.020	20 mm	<input type="checkbox"/>	04.211.046	46 mm
<input type="checkbox"/>	04.211.022	22 mm	<input type="checkbox"/>	04.211.048	48 mm
<input type="checkbox"/>	04.211.024	24 mm	<input type="checkbox"/>	04.211.050	50 mm
<input type="checkbox"/>	04.211.026	26 mm	<input type="checkbox"/>	04.211.052	52 mm
<input type="checkbox"/>	04.211.028	28 mm	<input type="checkbox"/>	04.211.054	54 mm
<input type="checkbox"/>	04.211.030	30 mm	<input type="checkbox"/>	04.211.056	56 mm
<input type="checkbox"/>	04.211.032	32 mm	<input type="checkbox"/>	04.211.058	58 mm
<input type="checkbox"/>	04.211.034	34 mm	<input type="checkbox"/>	04.211.060	60 mm

2.7 mm Titanium Cortex Screws, self-tapping, with T8 StarDrive recess



		LENGTH			LENGTH
<input type="checkbox"/>	402.870	10 mm	<input type="checkbox"/>	402.894	34 mm
<input type="checkbox"/>	402.872	12 mm	<input type="checkbox"/>	402.896	36 mm
<input type="checkbox"/>	402.874	14 mm	<input type="checkbox"/>	402.898	38 mm
<input type="checkbox"/>	402.876	16 mm	<input type="checkbox"/>	402.900	40 mm
<input type="checkbox"/>	402.878	18 mm	<input type="checkbox"/>	402.962	42 mm
<input type="checkbox"/>	402.880	20 mm	<input type="checkbox"/>	402.963	44 mm
<input type="checkbox"/>	402.882	22 mm	<input type="checkbox"/>	402.965	46 mm
<input type="checkbox"/>	402.884	24 mm	<input type="checkbox"/>	402.966	48 mm
<input type="checkbox"/>	402.886	26 mm	<input type="checkbox"/>	402.967	50 mm
<input type="checkbox"/>	402.888	28 mm	<input type="checkbox"/>	402.968	55 mm
<input type="checkbox"/>	402.890	30 mm	<input type="checkbox"/>	402.969	60 mm
<input type="checkbox"/>	402.892	32 mm			

2.4 mm Titanium Variable Angle Locking Screws, self-tapping, with T8 StarDrive recess



		LENGTH			LENGTH
<input type="checkbox"/>	04.210.110	10 mm	<input type="checkbox"/>	04.210.136	36 mm
<input type="checkbox"/>	04.210.112	12 mm	<input type="checkbox"/>	04.210.138	38 mm
<input type="checkbox"/>	04.210.114	14 mm	<input type="checkbox"/>	04.210.140	40 mm
<input type="checkbox"/>	04.210.116	16 mm	<input type="checkbox"/>	04.210.142	42 mm
<input type="checkbox"/>	04.210.118	18 mm	<input type="checkbox"/>	04.210.144	44 mm
<input type="checkbox"/>	04.210.120	20 mm	<input type="checkbox"/>	04.210.146	46 mm
<input type="checkbox"/>	04.210.122	22 mm	<input type="checkbox"/>	04.210.148	48 mm
<input type="checkbox"/>	04.210.124	24 mm	<input type="checkbox"/>	04.210.150	50 mm
<input type="checkbox"/>	04.210.126	26 mm	<input type="checkbox"/>	04.210.152	52 mm
<input type="checkbox"/>	04.210.128	28 mm	<input type="checkbox"/>	04.210.154	54 mm
<input type="checkbox"/>	04.210.130	30 mm	<input type="checkbox"/>	04.210.156	56 mm
<input type="checkbox"/>	04.210.132	32 mm	<input type="checkbox"/>	04.210.158	58 mm
<input type="checkbox"/>	04.210.134	34 mm	<input type="checkbox"/>	04.210.160	60 mm

Inventory Control Form

2.4 mm/2.7 mm Titanium VA-LCP Forefoot/Midfoot Plating System

Implants (cont'd)

2.4 mm Titanium Cortex Screws,
self-tapping, with T8 StarDrive recess



	LENGTH		LENGTH		
<input type="checkbox"/>	401.760	10 mm	<input type="checkbox"/>	401.786	36 mm
<input type="checkbox"/>	401.762	12 mm	<input type="checkbox"/>	401.788	38 mm
<input type="checkbox"/>	401.764	14 mm	<input type="checkbox"/>	401.790	40 mm
<input type="checkbox"/>	401.766	16 mm	<input type="checkbox"/>	04.210.942	42 mm
<input type="checkbox"/>	401.768	18 mm	<input type="checkbox"/>	04.210.944	44 mm
<input type="checkbox"/>	401.770	20 mm	<input type="checkbox"/>	04.210.946	46 mm
<input type="checkbox"/>	401.772	22 mm	<input type="checkbox"/>	04.210.948	48 mm
<input type="checkbox"/>	401.774	24 mm	<input type="checkbox"/>	04.210.950	50 mm
<input type="checkbox"/>	401.776	26 mm	<input type="checkbox"/>	04.210.952	52 mm
<input type="checkbox"/>	401.778	28 mm	<input type="checkbox"/>	04.210.954	54 mm
<input type="checkbox"/>	401.780	30 mm	<input type="checkbox"/>	04.210.956	56 mm
<input type="checkbox"/>	401.782	32 mm	<input type="checkbox"/>	04.210.958	58 mm
<input type="checkbox"/>	401.784	34 mm	<input type="checkbox"/>	04.210.960	60 mm

Instruments

Drill Bits, quick coupling

<input type="checkbox"/>	310.26	2.7 mm, 100 mm	
<input type="checkbox"/>	310.530	2.4 mm, 100 mm	

Drill Bits with depth mark, quick coupling

<input type="checkbox"/>	323.062	2.0 mm, 140 mm	
<input type="checkbox"/>	310.509	1.8 mm, 110 mm	
<input type="checkbox"/>	292.56	1.6 mm K-Wire, trocar tip (10/pkg.)	