

Inventory Control Form

MultiLoc Humeral Nailing System



Patient Information:

Synthes (USA)
To Order: (800) 523-0322

Synthes (Canada) Ltd.
To Order: (800) 668-1119

Date: _____

Hospital: _____

Surgeon: _____

Procedure: _____

Implants

8.0 mm Titanium MultiLoc Proximal Humeral Nail, Cannulated, 160 mm, Sterile



			LENGTH
<input type="checkbox"/>	04.016.034S	Right	160 mm
<input type="checkbox"/>	04.016.035S	Left	160 mm

9.5 mm Titanium MultiLoc Proximal Humeral Nail, Cannulated, 160 mm, Sterile



			LENGTH
<input type="checkbox"/>	04.016.038S	Right	160 mm
<input type="checkbox"/>	04.016.039S	Left	160 mm

7.0 mm Titanium MultiLoc Humeral Nail, Cannulated, Sterile



	RIGHT	LENGTH		LEFT	LENGTH
<input type="checkbox"/>	04.016.180S	180 mm	<input type="checkbox"/>	04.017.180S	180 mm
<input type="checkbox"/>	04.016.195S	195 mm	<input type="checkbox"/>	04.017.195S	195 mm
<input type="checkbox"/>	04.016.210S	210 mm	<input type="checkbox"/>	04.017.210S	210 mm
<input type="checkbox"/>	04.016.225S	225 mm	<input type="checkbox"/>	04.017.225S	225 mm
<input type="checkbox"/>	04.016.240S	240 mm	<input type="checkbox"/>	04.017.240S	240 mm
<input type="checkbox"/>	04.016.255S	255 mm	<input type="checkbox"/>	04.017.255S	255 mm
<input type="checkbox"/>	04.016.270S	270 mm	<input type="checkbox"/>	04.017.270S	270 mm
<input type="checkbox"/>	04.016.285S	285 mm	<input type="checkbox"/>	04.017.285S	285 mm
<input type="checkbox"/>	04.016.300S	300 mm	<input type="checkbox"/>	04.017.300S	300 mm
<input type="checkbox"/>	04.016.315S	315 mm	<input type="checkbox"/>	04.017.315S	315 mm

8.5 mm Titanium MultiLoc Humeral Nail, Cannulated, Sterile



	RIGHT	LENGTH		LEFT	LENGTH
<input type="checkbox"/>	04.018.180S	180 mm	<input type="checkbox"/>	04.019.180S	180 mm
<input type="checkbox"/>	04.018.195S	195 mm	<input type="checkbox"/>	04.019.195S	195 mm
<input type="checkbox"/>	04.018.210S	210 mm	<input type="checkbox"/>	04.019.210S	210 mm
<input type="checkbox"/>	04.018.225S	225 mm	<input type="checkbox"/>	04.019.225S	225 mm
<input type="checkbox"/>	04.018.240S	240 mm	<input type="checkbox"/>	04.019.240S	240 mm
<input type="checkbox"/>	04.018.255S	255 mm	<input type="checkbox"/>	04.019.255S	255 mm
<input type="checkbox"/>	04.018.270S	270 mm	<input type="checkbox"/>	04.019.270S	270 mm
<input type="checkbox"/>	04.018.285S	285 mm	<input type="checkbox"/>	04.019.285S	285 mm
<input type="checkbox"/>	04.018.300S	300 mm	<input type="checkbox"/>	04.019.300S	300 mm
<input type="checkbox"/>	04.018.315S	315 mm	<input type="checkbox"/>	04.019.315S	315 mm

Titanium MultiLoc End Caps, Sterile



		EXTENSION (MM)			EXTENSION (MM)
<input type="checkbox"/>	04.019.000S	0	<input type="checkbox"/>	04.019.010S	10
<input type="checkbox"/>	04.019.002S	2	<input type="checkbox"/>	04.019.015S	15
<input type="checkbox"/>	04.019.005S	5			

Implants (cont'd)

4.5 mm Titanium MultiLoc Screws \diamond



	LENGTH		LENGTH		
<input type="checkbox"/>	04.019.020	20 mm	<input type="checkbox"/>	04.019.042	42 mm
<input type="checkbox"/>	04.019.022	22 mm	<input type="checkbox"/>	04.019.044	44 mm
<input type="checkbox"/>	04.019.024	24 mm	<input type="checkbox"/>	04.019.046	46 mm
<input type="checkbox"/>	04.019.026	26 mm	<input type="checkbox"/>	04.019.048	48 mm
<input type="checkbox"/>	04.019.028	28 mm	<input type="checkbox"/>	04.019.050	50 mm
<input type="checkbox"/>	04.019.030	30 mm	<input type="checkbox"/>	04.019.052	52 mm
<input type="checkbox"/>	04.019.032	32 mm	<input type="checkbox"/>	04.019.054	54 mm
<input type="checkbox"/>	04.019.034	34 mm	<input type="checkbox"/>	04.019.056	56 mm
<input type="checkbox"/>	04.019.036	36 mm	<input type="checkbox"/>	04.019.058	58 mm
<input type="checkbox"/>	04.019.038	38 mm	<input type="checkbox"/>	04.019.060	60 mm
<input type="checkbox"/>	04.019.040	40 mm			

3.5 mm Titanium Locking Screws, Self-tapping with StarDrive recess \diamond



	LENGTH		LENGTH		
<input type="checkbox"/>	412.109	26 mm	<input type="checkbox"/>	412.117	40 mm
<input type="checkbox"/>	412.110	28 mm	<input type="checkbox"/>	412.118	42 mm
<input type="checkbox"/>	412.111	30 mm	<input type="checkbox"/>	412.134	44 mm
<input type="checkbox"/>	412.112	32 mm	<input type="checkbox"/>	412.136	46 mm
<input type="checkbox"/>	412.113	34 mm	<input type="checkbox"/>	412.120	48 mm
<input type="checkbox"/>	412.115	36 mm	<input type="checkbox"/>	412.121	50 mm
<input type="checkbox"/>	412.116	38 mm	<input type="checkbox"/>	412.122	52 mm

4.0 mm Titanium Locking Screws, with T25 StarDrive recess, for IM Nails \diamond



	LENGTH		LENGTH		
<input type="checkbox"/>	04.005.408	18 mm	<input type="checkbox"/>	04.005.436	46 mm
<input type="checkbox"/>	04.005.410	20 mm	<input type="checkbox"/>	04.005.438	48 mm
<input type="checkbox"/>	04.005.412	22 mm	<input type="checkbox"/>	04.005.440	50 mm
<input type="checkbox"/>	04.005.414	24 mm	<input type="checkbox"/>	04.005.442	52 mm
<input type="checkbox"/>	04.005.416	26 mm	<input type="checkbox"/>	04.005.444	54 mm
<input type="checkbox"/>	04.005.418	28 mm	<input type="checkbox"/>	04.005.446	56 mm
<input type="checkbox"/>	04.005.420	30 mm	<input type="checkbox"/>	04.005.448	58 mm
<input type="checkbox"/>	04.005.422	32 mm	<input type="checkbox"/>	04.005.450	60 mm
<input type="checkbox"/>	04.005.424	34 mm	<input type="checkbox"/>	04.005.452	62 mm
<input type="checkbox"/>	04.005.426	36 mm	<input type="checkbox"/>	04.005.454	64 mm
<input type="checkbox"/>	04.005.428	38 mm	<input type="checkbox"/>	04.005.456	66 mm
<input type="checkbox"/>	04.005.430	40 mm	<input type="checkbox"/>	04.005.458	68 mm
<input type="checkbox"/>	04.005.432	42 mm	<input type="checkbox"/>	04.005.460	70 mm
<input type="checkbox"/>	04.005.434	44 mm			

Instruments

Drill Bits

<input type="checkbox"/>	03.019.003	10.0 mm Hollow Drill Bit, for MultiLoc Humeral Nailing System	
<input type="checkbox"/>	03.019.004	11.5 mm Hollow Drill Bit, for 9.5 mm MultiLoc Proximal Humeral Nail	
<input type="checkbox"/>	03.019.016	3.8 mm Three-Fluted Drill Bit, Quick Coupling, Calibrated, length 270 mm, for 03.019.014	
<input type="checkbox"/>	03.019.018	6.5 mm Drill Bit, Conical, with Stop	
<input type="checkbox"/>	03.010.060	3.2 mm Three-Fluted Drill Bit, Quick Coupling, 330 mm, 100 mm Calibration	
<input type="checkbox"/>	03.010.103	3.2 mm Three-Fluted Drill Bits, Quick Coupling, 145 mm	
<input type="checkbox"/>	310.284	2.8 mm Drill Bit, Quick Coupling, 165 mm	

Guide Rod

<input type="checkbox"/>	03.019.026	2.5 mm Guide Rod with Stop, Trocar Tip, 280 mm length, for hollow drill bit	
--------------------------	------------	---	--

Kirschner Wires

<input type="checkbox"/>	292.16	1.6 mm Kirschner Wire, 150 mm, Trocar Point	
<input type="checkbox"/>	292.26	2.5 mm Kirschner Wire, 285 mm, Trocar Point	

Reaming Rod

<input type="checkbox"/>	351.709S	2.5 mm Reaming Rod, with stop, ball tip, sterile, 650 mm	
--------------------------	----------	--	--