

Inventory Control Form

Angular Stable Locking Screw System



Patient Information:

Synthes (USA)
To Order: (800) 523-0322

Synthes (Canada) Ltd.
To Order: (800) 668-1119

Date: _____

Hospital: _____

Surgeon: _____

Procedure: _____

Implants

4.0 mm Angular Stable Locking Screws, T25 StarDrive recess, for IM Nails, sterile



	LENGTH		LENGTH
<input type="checkbox"/>	04.025.416S 26 mm	<input type="checkbox"/>	04.025.444S 54 mm
<input type="checkbox"/>	04.025.418S 28 mm	<input type="checkbox"/>	04.025.446S 56 mm
<input type="checkbox"/>	04.025.420S 30 mm	<input type="checkbox"/>	04.025.448S 58 mm
<input type="checkbox"/>	04.025.422S 32 mm	<input type="checkbox"/>	04.025.450S 60 mm
<input type="checkbox"/>	04.025.424S 34 mm	<input type="checkbox"/>	04.025.452S 62 mm
<input type="checkbox"/>	04.025.426S 36 mm	<input type="checkbox"/>	04.025.454S 64 mm
<input type="checkbox"/>	04.025.428S 38 mm	<input type="checkbox"/>	04.025.456S 66 mm
<input type="checkbox"/>	04.025.430S 40 mm	<input type="checkbox"/>	04.025.458S 68 mm
<input type="checkbox"/>	04.025.432S 42 mm	<input type="checkbox"/>	04.025.460S 70 mm
<input type="checkbox"/>	04.025.434S 44 mm	<input type="checkbox"/>	04.025.462S 72 mm
<input type="checkbox"/>	04.025.436S 46 mm	<input type="checkbox"/>	04.025.464S 74 mm
<input type="checkbox"/>	04.025.438S 48 mm	<input type="checkbox"/>	04.025.466S 76 mm
<input type="checkbox"/>	04.025.440S 50 mm	<input type="checkbox"/>	04.025.468S 78 mm
<input type="checkbox"/>	04.025.442S 52 mm	<input type="checkbox"/>	04.025.470S 80 mm

6.0 mm Angular Stable Locking Screws, T25 StarDrive recess, for IM Nails, sterile



	LENGTH		LENGTH
<input type="checkbox"/>	04.025.622S 32 mm	<input type="checkbox"/>	04.025.656S 66 mm
<input type="checkbox"/>	04.025.624S 34 mm	<input type="checkbox"/>	04.025.658S 68 mm
<input type="checkbox"/>	04.025.626S 36 mm	<input type="checkbox"/>	04.025.660S 70 mm
<input type="checkbox"/>	04.025.628S 38 mm	<input type="checkbox"/>	04.025.662S 72 mm
<input type="checkbox"/>	04.025.630S 40 mm	<input type="checkbox"/>	04.025.664S 74 mm
<input type="checkbox"/>	04.025.632S 42 mm	<input type="checkbox"/>	04.025.666S 76 mm
<input type="checkbox"/>	04.025.634S 44 mm	<input type="checkbox"/>	04.025.668S 78 mm
<input type="checkbox"/>	04.025.636S 46 mm	<input type="checkbox"/>	04.025.670S 80 mm
<input type="checkbox"/>	04.025.638S 48 mm	<input type="checkbox"/>	04.025.675S 85 mm
<input type="checkbox"/>	04.025.640S 50 mm	<input type="checkbox"/>	04.025.680S 90 mm
<input type="checkbox"/>	04.025.642S 52 mm	<input type="checkbox"/>	04.025.685S 95 mm
<input type="checkbox"/>	04.025.644S 54 mm	<input type="checkbox"/>	04.025.690S 100 mm
<input type="checkbox"/>	04.025.646S 56 mm	<input type="checkbox"/>	04.025.695S 105 mm
<input type="checkbox"/>	04.025.648S 58 mm	<input type="checkbox"/>	04.025.700S 110 mm
<input type="checkbox"/>	04.025.650S 60 mm	<input type="checkbox"/>	04.025.705S 115 mm
<input type="checkbox"/>	04.025.652S 62 mm	<input type="checkbox"/>	04.025.710S 120 mm
<input type="checkbox"/>	04.025.654S 64 mm	<input type="checkbox"/>	04.025.715S 125 mm

5.0 mm Angular Stable Locking Screws, T25 StarDrive recess, for IM Nails, sterile



	LENGTH		LENGTH
<input type="checkbox"/>	04.025.520S 30 mm	<input type="checkbox"/>	04.025.550S 60 mm
<input type="checkbox"/>	04.025.522S 32 mm	<input type="checkbox"/>	04.025.552S 62 mm
<input type="checkbox"/>	04.025.524S 34 mm	<input type="checkbox"/>	04.025.554S 64 mm
<input type="checkbox"/>	04.025.526S 36 mm	<input type="checkbox"/>	04.025.556S 66 mm
<input type="checkbox"/>	04.025.528S 38 mm	<input type="checkbox"/>	04.025.558S 68 mm
<input type="checkbox"/>	04.025.530S 40 mm	<input type="checkbox"/>	04.025.560S 70 mm
<input type="checkbox"/>	04.025.532S 42 mm	<input type="checkbox"/>	04.025.562S 72 mm
<input type="checkbox"/>	04.025.534S 44 mm	<input type="checkbox"/>	04.025.564S 74 mm
<input type="checkbox"/>	04.025.536S 46 mm	<input type="checkbox"/>	04.025.566S 76 mm
<input type="checkbox"/>	04.025.538S 48 mm	<input type="checkbox"/>	04.025.568S 78 mm
<input type="checkbox"/>	04.025.540S 50 mm	<input type="checkbox"/>	04.025.570S 80 mm
<input type="checkbox"/>	04.025.542S 52 mm	<input type="checkbox"/>	04.025.575S 85 mm
<input type="checkbox"/>	04.025.544S 54 mm	<input type="checkbox"/>	04.025.580S 90 mm
<input type="checkbox"/>	04.025.546S 56 mm	<input type="checkbox"/>	04.025.585S 95 mm
<input type="checkbox"/>	04.025.548S 58 mm	<input type="checkbox"/>	04.025.590S 100 mm

Resorbable Sleeves, sterile, 2/pkg.



<input type="checkbox"/>	08.025.032S	For 4.0 mm ASLS
<input type="checkbox"/>	08.025.044S	For 5.0 mm ASLS
<input type="checkbox"/>	08.025.057S	For 6.0 mm ASLS

Instruments

Drill-Reamers

For use with Radiolucent Drive

<input type="checkbox"/>	03.025.037	2.9 mm/5.0 mm, for 4.0 mm ASLS
<input type="checkbox"/>	03.025.038	3.9 mm/6.0 mm, for 5.0 mm ASLS
<input type="checkbox"/>	03.025.039	4.9 mm/7.0 mm, for 6.0 mm ASLS



Quick coupling

<input type="checkbox"/>	03.025.134	2.9 mm/5.0 mm, for 4.0 mm ASLS
<input type="checkbox"/>	03.025.135	3.9 mm/6.0 mm, for 5.0 mm ASLS
<input type="checkbox"/>	03.025.136	4.9 mm/7.0 mm, for 6.0 mm ASLS

Three-Fluted Drill Bits

Quick coupling, 150 mm

<input type="checkbox"/>	03.025.082	2.9 mm/3.2 mm, for 4.0 mm ASLS
<input type="checkbox"/>	03.025.083	3.9 mm/4.2 mm, for 5.0 mm ASLS
<input type="checkbox"/>	03.025.084	4.9 mm/5.0 mm, for 6.0 mm ASLS



Quick coupling, 331 mm/100 mm calibration

<input type="checkbox"/>	03.025.104	2.9 mm/3.2 mm, for 4.0 mm ASLS
<input type="checkbox"/>	03.025.105	3.9 mm/4.2 mm, for 5.0 mm ASLS
<input type="checkbox"/>	03.025.106	4.9 mm/5.0 mm, for 6.0 mm ASLS



For use with Radiolucent Drive, 145 mm

<input type="checkbox"/>	03.025.124	2.9 mm/3.2 mm, for 4.0 mm ASLS
<input type="checkbox"/>	03.025.125	3.9 mm/4.2 mm, for 5.0 mm ASLS
<input type="checkbox"/>	03.025.126	4.9 mm/5.0 mm, for 6.0 mm ASLS

Drill-Reamers

Quick coupling, 145 mm

<input type="checkbox"/>	03.025.027	2.9 mm/5.0 mm, for 4.0 mm ASLS
<input type="checkbox"/>	03.025.028	3.9 mm/6.0 mm, for 5.0 mm ASLS
<input type="checkbox"/>	03.025.029	4.9 mm/7.0 mm, for 6.0 mm ASLS

