

Inventory Control Form

4.5 mm VA LCP® Curved Condylar Plate System with OPTILINK™ Screw Technology

Case Information (eg, Case ID):

DO NOT PUT ANY
PATIENT IDENTIFIABLE
INFORMATION IN
THIS FIELD

To order (USA): 800-523-0322

To order (Canada): 844-243-4321

Date: _____

Hospital: _____

Surgeon: _____

Procedure: _____

Implants

4.5 mm VA LCP® Titanium Curved Condylar Plates

Available nonsterile or sterile-packed. Add "S" to catalog number to order sterile product.



		Holes	Length
<input type="checkbox"/>	04.124.406	6, Right	159 mm
<input type="checkbox"/>	04.124.407	6, Left	159 mm
<input type="checkbox"/>	04.124.408	8, Right	195 mm
<input type="checkbox"/>	04.124.409	8, Left	195 mm
<input type="checkbox"/>	04.124.410	10, Right	230 mm
<input type="checkbox"/>	04.124.411	10, Left	230 mm
<input type="checkbox"/>	04.124.412	12, Right	266 mm
<input type="checkbox"/>	04.124.413	12, Left	266 mm
<input type="checkbox"/>	04.124.414	14, Right	301 mm
<input type="checkbox"/>	04.124.415	14, Left	301 mm
<input type="checkbox"/>	04.124.416	16, Right	336 mm
<input type="checkbox"/>	04.124.417	16, Left	336 mm
<input type="checkbox"/>	04.124.418	18, Right	370 mm
<input type="checkbox"/>	04.124.419	18, Left	370 mm

The following products are available sterile only:

<input type="checkbox"/>	04.124.420S	20, Right	405 mm
<input type="checkbox"/>	04.124.421S	20, Left	405 mm
<input type="checkbox"/>	04.124.422S	22, Right	439 mm
<input type="checkbox"/>	04.124.423S	22, Left	439 mm

5.0 mm Periprosthesis Variable Angle Locking Screws, OPTILINK™, self-tapping, T25 StarDrive™

Available nonsterile or sterile-packed. Add "S" to catalog number to order sterile product.



		Length		Length	
<input type="checkbox"/>	42.231.010	10 mm	<input type="checkbox"/>	42.231.016	16 mm
<input type="checkbox"/>	42.231.012	12 mm	<input type="checkbox"/>	42.231.018	18 mm
<input type="checkbox"/>	42.231.014	14 mm			

The following product is available sterile only:

<input type="checkbox"/>	42.231.008S	8 mm
--------------------------	-------------	------

5.0 mm Variable Angle Locking Screws, OPTILINK™, self-tapping, T25 StarDrive



		Length		Length	
<input type="checkbox"/>	42.231.214	14 mm	<input type="checkbox"/>	42.231.242	42 mm
<input type="checkbox"/>	42.231.216	16 mm	<input type="checkbox"/>	42.231.244	44 mm
<input type="checkbox"/>	42.231.218	18 mm	<input type="checkbox"/>	42.231.246	46 mm
<input type="checkbox"/>	42.231.220	20 mm	<input type="checkbox"/>	42.231.248	48 mm
<input type="checkbox"/>	42.231.222	22 mm	<input type="checkbox"/>	42.231.250	50 mm
<input type="checkbox"/>	42.231.224	24 mm	<input type="checkbox"/>	42.231.255	55 mm
<input type="checkbox"/>	42.231.226	26 mm	<input type="checkbox"/>	42.231.260	60 mm
<input type="checkbox"/>	42.231.228	28 mm	<input type="checkbox"/>	42.231.265	65 mm
<input type="checkbox"/>	42.231.230	30 mm	<input type="checkbox"/>	42.231.270	70 mm
<input type="checkbox"/>	42.231.232	32 mm	<input type="checkbox"/>	42.231.275	75 mm
<input type="checkbox"/>	42.231.234	34 mm	<input type="checkbox"/>	42.231.280	80 mm
<input type="checkbox"/>	42.231.236	36 mm	<input type="checkbox"/>	42.231.285	85 mm
<input type="checkbox"/>	42.231.238	38 mm	<input type="checkbox"/>	42.231.290	90 mm
<input type="checkbox"/>	42.231.240	40 mm			

The following products are available sterile only:

<input type="checkbox"/>	42.231.295S	95 mm	<input type="checkbox"/>	42.231.305S	105 mm
<input type="checkbox"/>	42.231.300S	100 mm	<input type="checkbox"/>	42.231.310S	110 mm

Inventory Control Form

4.5 mm VA LCP® Curved Condylar Plate System with OPTILINK™ Screw Technology

Implants (cont'd)

5.0 mm Cannulated Variable Angle Locking Screws, OPTILINK™



	Length		Length
<input type="checkbox"/>	42.231.620 20 mm	<input type="checkbox"/>	42.231.660 60 mm
<input type="checkbox"/>	42.231.625 25 mm	<input type="checkbox"/>	42.231.665 65 mm
<input type="checkbox"/>	42.231.630 30 mm	<input type="checkbox"/>	42.231.670 70 mm
<input type="checkbox"/>	42.231.635 35 mm	<input type="checkbox"/>	42.231.675 75 mm
<input type="checkbox"/>	42.231.640 40 mm	<input type="checkbox"/>	42.231.680 80 mm
<input type="checkbox"/>	42.231.645 45 mm	<input type="checkbox"/>	42.231.685 85 mm
<input type="checkbox"/>	42.231.650 50 mm	<input type="checkbox"/>	42.231.690 90 mm
<input type="checkbox"/>	42.231.655 55 mm		

The following products are available sterile only:

<input type="checkbox"/>	42.231.695S 95 mm	<input type="checkbox"/>	42.231.705S 105 mm
<input type="checkbox"/>	42.231.700S 100 mm	<input type="checkbox"/>	42.231.710S 110 mm

4.5 mm Cortex Screws, self tapping, 3.5 Hex



	Length		Length
<input type="checkbox"/>	414.822 22 mm	<input type="checkbox"/>	414.848 48 mm
<input type="checkbox"/>	414.824 24 mm	<input type="checkbox"/>	414.850 50 mm
<input type="checkbox"/>	414.826 26 mm	<input type="checkbox"/>	414.852 52 mm
<input type="checkbox"/>	414.828 28 mm	<input type="checkbox"/>	414.854 54 mm
<input type="checkbox"/>	414.830 30 mm	<input type="checkbox"/>	414.856 56 mm
<input type="checkbox"/>	414.832 32 mm	<input type="checkbox"/>	414.858 58 mm
<input type="checkbox"/>	414.834 34 mm	<input type="checkbox"/>	414.860 60 mm
<input type="checkbox"/>	414.836 36 mm	<input type="checkbox"/>	414.862 62 mm
<input type="checkbox"/>	414.838 38 mm	<input type="checkbox"/>	414.864 64 mm
<input type="checkbox"/>	414.840 40 mm	<input type="checkbox"/>	414.866 66 mm
<input type="checkbox"/>	414.842 42 mm	<input type="checkbox"/>	414.868 68 mm
<input type="checkbox"/>	414.844 44 mm	<input type="checkbox"/>	414.870 70 mm
<input type="checkbox"/>	414.846 46 mm		

Instruments

Drill Bits and Wires

<input type="checkbox"/>	310.243	2.5 mm Drill Tip Guide Wire, 200 mm
<input type="checkbox"/>	310.31	3.2 mm Drill Bit, 145 mm, quick coupling
<input type="checkbox"/>	310.431	4.3 mm Drill Bit, 180 mm, quick coupling
<input type="checkbox"/>	324.212	3.2 mm Percutaneous Drill Bit QC/300 mm/ calibrated
<input type="checkbox"/>	324.213	4.3 mm Percutaneous Drill Bit QC/300 mm/ calibrated
<input type="checkbox"/>	292.652	2.0 mm Non colored, threaded guide wire, spade point, 230 mm
<input type="checkbox"/>	310.44	4.5 mm Drill Bit, 145 mm, quick coupling
<input type="checkbox"/>	310.634	4.3 mm Cannulated Drill Bit, quick coupling, 200 mm
<input type="checkbox"/>	310.632	5.0 Cannulated Drill Bit, quick coupling, 200 mm
<input type="checkbox"/>	03.120.026	2.5 mm Drill Tip Guide Wire, 300 mm

Some devices in this form may not have been licensed in accordance with Canadian law and may not be for sale in Canada. Please contact your sales consultant for items approved for sale in Canada.